





























Familles produits	Spécifications	Pas (mm)	Configurations de montage				Raccordements			Applications	
											
	Colibri COM Express	0.5	✓				✓				✓ 5 Gbit/s
	DIN41612 CEI 60603-2 VMEbus Technology	2.54 / 5.08	✓	✓	✓			✓	✓	✓ 1.5 A to 15 A	
	flexilink jumper -	2			✓			✓		✓ 8 A	
	VarPol -	2 / 2.54	✓	✓				✓	✓	✓ 1.9 A	
	PC/104 PC/104-Plus  	2 / 2.54	✓					✓	✓	✓ 1.7 A to 1.9 A	
	TCA ATCA μ TCA	0.75 / 3		✓		✓		✓		✓ 12 A to 16 A	✓ 12.5 Gbit/s
	hm2.0 CEI 61076-4-101 CompactPCI	2		✓				✓			✓ bis 3 Gbit/s
	Velox VITA46 VPX	1.8		✓				✓			✓ 10 Gbit/s
	Power Terminals -	5.08						✓		✓ 15 A to 45 A	
	Outillages d'insertion -	-									



Configurations de montage

-  Parallèle
-  Perpendiculaire
-  Horizontale
-  Encartable

Raccordements

-  CMS
-  Press fit
-  Traversant

Applications

-  Puissance
-  Haut débit