



### Vacuum Test Fixtures for TS 12x/LH/GR 228x

<b>Part No. 8852</b>	VA 2040/F/H/GR 228x 15/07 Slots	Usable Area: 440 x 340 mm* Outside Dimensions: 550 x 450 x 110 mm (w x d x h)
<b>Part No. 12833</b>	VA 2040/F/H/GR 228x 15/15 Slots	Usable Area: 440 x 340 mm* Outside Dimensions: 550 x 450 x 100 mm (w x d x h)
<b>Part No. 19533</b>	VA 2040/F/H/GR 228x 18/07 Slots	Usable Area: 440 x 340 mm* Outside Dimensions: 550 x 450 x 100 mm (w x d x h)
<b>Part No. 15980</b>	VA 2040/F/H/GR 228x 18/18 Slots	Usable Area: 440 x 340 mm* Outside Dimensions: 550 x 450 x 110 mm (w x d x h)
<b>Part No. 17013</b>	VA 2601-2/E/F/H/GR 228x 15/15 Slots (dual-stage Version)	Usable Area: 390 x 300 mm* Outside Dimensions: 550 x 450 x 115 mm (w x d x h)
<b>Part No. 3802</b>	VA 2030/F/H/GR 2270/71	Usable Area: 340 x 220 mm* Outside Dimensions: 480 x 370 x 90 mm (w x d x h)
<b>Part No. 3812</b>	VA 2040/F/H/GR 2270/71	Usable Area: 440 x 340 mm* Outside Dimensions: 567 x 488 x 92 mm (w x d x h)
<b>Part No. 4672</b>	VA 2130/F/H/GR 2270/71 (Tandem Version)	Usable Area: 130 x 200 mm per chamber (left/right)* Outside Dimensions: 480 x 370 x 90 mm (w x d x h)
<b>Part No. 4673</b>	VA 2140/F/H/GR 2270/71 (Tandem Version)	Usable Area: 180 x 340 mm per chamber (left/right)* Outside Dimensions: 550 x 490 x 90 mm (w x d x h)
<b>Part No. 13963</b>	VA 2601-2/E/F/H/GR 2270/71 (dual-stage Version)	Usable Area: 390 x 300 mm* Outside Dimensions: 550 x 450 x 95 mm (w x d x h)

Vacuum Interchangeable Fixtures available.

### Manual Test Fixtures

<b>Part No. 33462</b>	MA 2112/D/H/S-7/GR2270/71	Usable Area: 295 x 250 mm* Outside Dimensions: 483 x 548 x 262 mm (w x d x h)
<b>Part No. 33674</b>	MA 2112-2/D/H/S-7/GR2270/71	Usable Area: 295 x 250 mm* Outside Dimensions: 483 x 548 x 262 mm (w x d x h)
<b>Part No. 32920</b>	MA 2113/D/H/S-10/GR2270/71	Usable Area: 450 x 320 mm* Outside Dimensions: 633 x 620 x 277 mm (w x d x h)
<b>Part No. 33675</b>	MA 2113-2/D/H/S-10/GR2270/71	Usable Area: 450 x 320 mm* Outside Dimensions: 633 x 620 x 277 mm (w x d x h)
<b>Part No. 33543</b>	MA 2113T/D/H/2xS-5/GR2270/71 (Tandem Version)	Usable Area: 155 x 250 mm* (each) Outside Dimensions: 633 x 564 x 283 mm (w x d x h)

#### Customizing Accessories for Open Express

<b>Part No. 19941</b>	Open Express Board Kit (Viper, incl. Cable)
<b>Part No. 22373</b>	OFM BOARD for GenRad
<b>Part No. 23433</b>	Open Express 1.2

\* The outside dimensions of the PC-Board can in some cases be larger than the stated usable area.

#### Contact Terminals for post-loading of Interface GR 228x

<b>Part No. 17513</b>	Contact Terminals for Signal Field
<b>Part No. 3609</b>	Contact Terminals for Power Field

#### Fixture Interface components GR 2270/71

<b>Part No. 13515</b>	S-ATS-170-06, Signal Block (Contact Terminal with bore hole)
-----------------------	--------------------------------------------------------------

#### Test System Interface Probe

**GKS 938 307 180 A 1500**