



Vacuum Test Fixtures:

VA 2030/F/H/R&S

Part No. 4116 Usable Area: 340 x 220 mm*; Outside Dimensions: 480 x 370 x 90 mm (w x d x h)

VA 2040/F/H/R&S

Part No. 1226 Usable Area: 430 x 340 mm*; Outside Dimensions: 550 x 490 x 90 mm (w x d x h)

VA 2040/F/H/R&S for 19"

Part No. 16124 Vacuum Fixture for 19" Housing
Usable Area: 430 x 340 mm*; Outside Dimensions: 550 x 535 x 90 mm (w x d x h)

VA 2601-2/E/F/H/R&S (dual-stage Version)

Part No. 16001 Usable Area: 390 x 300 mm*; Outside Dimensions: 550 x 490 x 95 mm (w x d x h)

VA 2601-2/E/F/H/R&S-19" (dual-stage Version)

Part No. 16198 Usable Area: 390 x 300 mm*; Outside Dimensions: 550 x 535 x 95 mm (w x d x h)

Manual Test Fixtures:

MA 2112/D/H/S-7/Pylon 9,6

Part No. 33681 Usable Area: 295 x 250 mm*; Outside Dimensions: 483 x 548 x 262 mm (w x d x h)

Replacement Kits see page 10.

Interface Materials

Part No. 13515 S-ATS-170-06, Signal Block loaded with KT-158 06

Further Interface Pin Blocks can be found on page 43.

Test System Interface Probe

GKS-945 357 106 A 1100

* The outside dimensions of the PC-Board can in some cases be larger than the stated usable area.



VA 2030/F/H/R&S