


STANDARD CONNECTOR PROBES

Dimensions & Specifications

▶ 101582 PROBE



PROBE SPECIFICATIONS

Minimum Centers	0.07 (1.78) 0.05 (1.27) staggered rows
Current Rating	9 A continuous <i>(individual probe in free air @ ambient temperature)</i>
Spring Force	48 g @ 0.03 (0.76) travel
Typical Resistance	< 10 mΩ
Maximum Travel	0.03 (0.76)
Working Travel	0.03 (0.76)


MATERIALS

Barrel	Brass, gold plated
Spring	Stainless steel
Plungers	Beryllium copper, gold plated

HOW TO ORDER

Part Number	101582-000
--------------------	------------

▶ 101438 PROBE



PROBE SPECIFICATIONS

Minimum Centers	0.08 (2.03)
Current Rating	1 A continuous <i>(individual probe in free air @ ambient temperature)</i>
Spring Force	99 g @ 0.02 (0.51) travel
Typical Resistance	< 10 mΩ
Maximum Travel	0.039 (0.99)
Working Travel	0.02 (0.51)

MATERIALS

Barrel	Brass, gold plated
Spring	Stainless steel, gold plated
Plunger	Beryllium copper, gold plated

HOW TO ORDER

Part Number	101438-000
--------------------	------------