


▶ 101506 PROBE



PROBE SPECIFICATIONS

<b>Minimum Centers</b>	0.05 (1.27)
<b>Current Rating</b>	5 A continuous <i>(individual probe in free air @ ambient temperature)</i>
<b>Spring Force</b>	39 g @ 0.02 (0.51) travel
<b>Typical Resistance</b>	< 20 mΩ
<b>Maximum Travel</b>	0.028 (0.71)
<b>Working Travel</b>	0.02 (0.51)


MATERIALS

<b>Barrel</b>	Nickel/silver, gold plated
<b>Spring</b>	Stainless steel, gold plated
<b>Plunger</b>	Beryllium copper, gold plated

HOW TO ORDER

<b>Part Number</b>	101506-000
--------------------	------------

▶ 101294 PROBE



PROBE SPECIFICATIONS

<b>Minimum Centers</b>	0.05 (1.27)
<b>Current Rating</b>	5 A continuous <i>(individual probe in free air @ ambient temperature)</i>
<b>Spring Force</b>	26 g @ 0.02 (0.51) travel
<b>Typical Resistance</b>	< 20 mΩ
<b>Maximum Travel</b>	0.027 (0.69)
<b>Working Travel</b>	0.02 (0.51)

MATERIALS

<b>Barrel</b>	Nickel/silver, gold plated
<b>Spring</b>	Stainless steel, gold plated
<b>Plunger</b>	Beryllium copper, gold plated

HOW TO ORDER

<b>Part Number</b>	101294-000
--------------------	------------