

Product Data Sheet

DIN 41612 Female straight, type G low profile,
Part No. 112-40584





Illustration similar



Perpendicular



Through Hole



Power



Rugged

- Termination length 4.6 mm
- 64 contacts
- solder
- performance level 2

Product Data Sheet

DIN 41612 Female straight, type G low profile,
Part No. 112-40584



Technical Specifications

Basics

Specification	IEC 60603-2 (DIN 41612)
Performance Level	2
No. of Contacts	64
Termination Technology	solder
Termination Length	4.6 mm
Operating Temperature Range	-55°C to +125°C

Material

Insulator Material	PBT glass filled UL 94 V-0
CTI value <i>IEC 60112</i>	200
Contact Material	Copper alloy

Mechanical

Pitch	5.08 x 3.81 mm
Mating Force	< 100 N
Separating Force per Pin	>0.2 N
Durability	400 mating cycles

Electrical

Operational Current	5.6 A
Contact Resistance	< 15 mΩ
Clearance and Creepage	cr: ≥ 3.0 mm, cl: ≥ 1.6 mm
Insulation Resistance	>10 ⁶ MΩ
Test Voltage	1550 V

Approval / Compliance


UL file	E130314
Environment	RoHS compliant

Product Data Sheet

DIN 41612 Female straight, type G low profile,
Part No. 112-40584



Derating Diagram



Product Data Sheet



DIN 41612 Female straight, type G low profile, Part No. 112-40584



Options

Board Lock

Suitable for connectors with type B, C, D, E, F low profile, G low profile, M female connectors and R male connectors



	Forces			Part Number	PCB Thickness
Type of Insertion	F_m	not soldered F_h	soldered F_h	112-40584C1	1.6 mm
Locked	< 20 N	> 10 N	> 25 N	112-40584C2	2.4 mm
Under Tension	< 20 N	> 5 N	> 25 N	112-40584C3	3.6 mm

Modifications

Available on request

- Without flange
- Special contact length
- Performance levels I + III or customer-specific
- Contact arrangement

Accessories

» DIN 41612 Coding type D, E, F and G
Part Number 106-10001

Product Data Sheet

DIN 41612 Female straight, type G low profile,
Part No. 112-40584

