


CP 412

ICT/FCT Standard Probes $\geq 2,54$ mm / ≥ 100 mil

Available Tip Styles

Material	Tip Style	Ø mm
B	A	1,00
		1,80
		2,00
B S	B	1,00
B	F	1,00
		1,80
		2,00
B	D	1,00
		1,80
		2,00
B S	E	1,80
		2,00
B	H	1,00
		1,80
		2,00
B	HB	2,00
B	T	2,00
B	LM	1,00
		1,80
		2,00
S	SP	1,00
S	SW	1,00
B S	V	1,00
		1,80
		2,00
B S	Y	1,00
		1,80
		2,00



Technical Data

Recommended minimum centers:	2,54 mm
Recommended working stroke:	8,00 mm
Maximum stroke:	10,00 mm
Current rating:	5,0 - 8,0 A
Typical contact resistance:	<20 mΩ
Operating temperature range:	-50° up to +100°

Materials

Plunger:	BeCu or Steel, nickel or gold plated
Barrel:	Brass, gold plated
Spring:	Music wire, gold plated
Receptacle:	Brass, gold plated

Spring Force (g $\pm 20\%$)

Spring force:	200 g
Alternative:	100 g
	150 g
	250 g
	300 g


Hole size without receptacle

Drills:	Ø1,66 - Ø1,67
---------	---------------

Hole size with receptacle (see page 38)

Drills:	Ø1,99 - Ø2,00
---------	---------------

* Collar Height	Total Length	Different collar heights and spacers (DR) are available to vary the total installation height of the probe.
2	37	
3	38	
5	40	
7	42	
10	45	



Ordering example:

Series	Tip Style	Material	Plating
CP 412	/5	B=BeCu S=Steel	G=Gold N=Nickel
Collar Height	200	200	G
Tip Ø mm	Spring Force		