



Basic Threaded Probes

F73206B200G150IK05

Order code 1009692

General

Design	Basic Contact Probe
Family	F732
Pitch [mm/mil]	2.54 / 100
Temperature [C°]	-45°C...+100°C
Additional definition	IK05

Electrical specifications

Continuous current [A]	5.00
Typical contact resistance [mOhm]	25.00

Mechanical specifications

Preload [cN]	60.00
Spring force [cN]	150.00
Nominal travel [mm]	4.00
Maximum travel [mm]	5.00
Pointing accuracy +/- [mm]	0.08
Thread	M1.6
Tool size [mm]	1.7

Dimensions


Total length [mm]	36.20
Projection height [mm]	10.80
Tip style diameter [mm]	2.00
Barrel diameter [mm]	1.65
Collar diameter [mm]	2.30
Press ring diameter [mm]	2.30

Materials & surfaces

Tip style	06
Plunger material	Beryllium copper
Plunger plating	Gold
Barrel material	Brass
Barrel plating	Gold
Spring material	Spring steel
Spring plating	Silver

Family drawing

All measurements are in mm.



Accessories

Tool for receptacle	FEWZ-772E0
Tool for probe	1001681-FWZ732, 1004610-FWZ732T
Other	1003076-H732LAS1

Tip style 1

