



Basic Contact Probes

F77203B130G300

Order code 1013940

General

Design	Basic Contact Probe
Family	F772
Pitch [mm/mil]	2.54 / 100
Temperature [C°]	-45°C...+80°C

Electrical specifications

Continuous current [A]	5.00
Typical contact resistance [mOhm]	20.00

Mechanical specifications

Preload [cN]	60.00
Spring force [cN]	300.00
Nominal travel [mm]	4.00
Maximum travel [mm]	5.00
Pointing accuracy +/- [mm]	0.08

Dimensions


Total length [mm]	32.00
Projection height [mm]	10.00
Tip style diameter [mm]	1.30
Barrel diameter [mm]	1.66
Collar diameter [mm]	2.05
Press ring diameter [mm]	2.05

Materials & surfaces

Tip style	03
Plunger material	Beryllium copper
Plunger plating	Gold
Barrel material	Nickel silver
Barrel plating	Gold
Spring material	Spring steel
Spring plating	Silver

Family drawing

All measurements are in mm.



Accessories

Tool for receptacle	FEWZ-772
Other	1007939-H772LAHC, 1043720-H772WW6.5-0.1, 1036005-H772LA-7.6, 1035995-H772WW-7.6, 1035994-H772CR-7.6

Tip style 1

