FEINMETALL
Contact Technologies



Switch Probes

F88617B590G350SM

Order code 1004216

General

Design	Basic Contact Probe
Family	F886-NO
Pitch [mm/mil]	3.50 / 138
Temperature [C°]	-45°C...+100°C
Additional definition	SM

Electrical specifications

Continuous current [A]	10.00
Typical contact resistance [mOhm]	50.00
Switch travel [mm]	1.70
Continuous current 2 [A]	1.00

Mechanical specifications

Preload [cN]	130.00
Spring force [cN]	350.00
Nominal travel [mm]	4.00
Maximum travel [mm]	5.00
Pointing accuracy +/- [mm]	0.09
Thread	M2.5
Tool size [mm]	2.6

Dimensions


Total length [mm]	44.80
Projection height [mm]	10.00
Tip style diameter [mm]	5.90
Barrel diameter [mm]	2.65
Collar diameter [mm]	3.20

Materials & surfaces

Tip style	17
Plunger material	Beryllium copper
Plunger plating	Gold
Barrel material	Brass
Barrel plating	Gold
Spring material	Spring steel
Spring plating	Silver

Family drawing

All measurements are in mm.



Accessories

Tool for probe	1004488-FWZ886, 1008409-FWZ886T
Other	1003080-H885KB, 1037131-H885KBAT, 1036356-H885KBIS, 1003079-H885IS, 1002935-H885KB-5

Copyright © 2026-10-19

Tip style 1



Copyright © 2026-10-19