

Grid:


≥ 2,54 mm

≥ 100 Mil

Installation height with KS: 10,5 - 26,3 mm (.413 - 1.035) / variable


Recommended stroke: 4,0 mm (.157)

Mounting and functional dimensions



Plug


VS-112 is used instead of a test probe to prevent receptacles being used unnecessarily during maintenance.



Collar height and installation height

Test probes with alternative collar heights are available to adjust the installation height of the tip (dimension without receptacle).

Collar height	Total length	Installation height without receptacle
02	32,3 mm (1.27)	10,3 mm (.406)
03	32,3 mm (1.27)	11,3 mm (.445)
04	34,3 mm (1.35)	12,3 mm (.484)
05	35,7 mm (1.40)	13,3 mm (.524)
06	36,3 mm (1.43)	14,3 mm (.563)
07	37,3 mm (1.47)	15,3 mm (.602)
08	38,7 mm (1.52)	16,3 mm (.642)
09	39,3 mm (1.55)	17,3 mm (.681)
10	40,3 mm (1.58)	18,3 mm (.720)



without KS

Available tip styles

Material	Tip style	Plating	Further versions	
			Ø	Ø (inch)
2 01		R A	Ø 1,00 (.039)	0,80 (.031)
3 02		A	Ø 0,80 (.031)	
3 02		A	Ø 2,00 (.079)	1,00 (.039) 1,50 (.059)
3 03		A	Ø 2,00 (.079)	1,40 (.055) 1,80 (.071)
2 04		R	Ø 2,00 (.079)	1,30 (.051)
3 05		A	Ø 0,64 (.025)	0,80 (.031)
3 05		A	Ø 2,00 (.079)	1,00 (.039) 1,40 (.055) 2,30 (.091)
0 06		A	Ø 2,30 (.091)	
3 06		A	Ø 2,00 (.079)	
3 06		R	Ø 2,00 (.079)	1,30 R (.051) 1,50 R (.059) 1,80 R (.071) 2,50 R (.098)
2 07		R A	Ø 2,00 (.079)	1,30 A (.051)
2 09		N	Ø 0,60 (.024)	
2 14		A	Ø 1,30 (.051)	1,30 R (.051)
2 17		N	Ø 1,75 (.069)	2,00 R (.079)
3 19		A	Ø 1,80 (.071)	2,00 A (.079)

** also available as tip style 0 02 and 0 03, installation height plus 0,8 mm (.031)

*** pressed-in steel point in base plunger made of brass

Mechanical data

Working stroke: 4,0 mm (.157)

Maximum stroke: 5,3 mm (.209)

Spring force at work. stroke: 1,5 N (5.4oz)

Alternative: 0,6 N (2.2oz); 0,8 N (2.9oz); 2,25 N (8.1oz); 3,0 N (10.8oz); 5,0 N (18.1oz)

Test probes with tip diameter ≤ 1,0 mm (.039) have a maximum stroke of 8,0 mm (.315)

Exception: 5,0 N-spring (18.1oz): max. stroke is always 5,3 mm (.209).

Materials

Plunger: BeCu or steel, gold-plated, rhodium- or chemically nickel-plated

Barrel: Nickel-silver or brass, gold-plated

Spring: Steel, gold-plated, stainless steel*(C)

Receptacle: Brass, gold-plated

Operating temperature

Standard: -40° up to +80° C

***with spec. designation "C":** -100° up to +200° C (0,8 N ; 1,5 N; 2,25 N; 3,0 N)

Electrical data

Current rating: 5 - 8 A

R_i typical: < 20 mΩ (* < 100 mΩ)

Note to GKS-112 and KS-112:

Receptacles in the KS-112 series are used for the GKS-112 (page 60) test probe series.

Note:

Screw-in versions shown on page 125.

Ordering example

Ordering example

Series	Tip material 0 = Delrin 2 = Steel 3 = BeCu	Tip style	Tip diameter (1/100 mm)	Plating A = Gold N = Nickel R = Rhodium	Spring force (dN)	Collar height (mm)	Special designation ("C")	
Test probe:	G K S	1 1 2	2 0 4	1 3 0	R	1 5	0 2	
Receptacle for GKS-112:	K S – 1 1 2 3 0		K S – 1 1 2 4 7					
Plug:	V S – 1 1 2							

All specifications are subject to change without prior notification